TIREBOSS™ TIRE PRESSURE CONTROL SYSTEM

DRIVI	FS NN		DA	ATE:									
TRUCK AS				JOTE #:									
COMPANY:			C	ONTA	.CT:								
MAILING ADDRESS:													
COUNTRY:													
PHONE:													
APPLICATION:													
VEHICLE	INFO			VE AXL			$\overline{\bot}$			NOT	ES		
MAKE:			DRIVE AXLE MAK				$\overline{-}$	_	_		_	_	
MODEL:	_YEAR:		MODEL:				_						ļ
REF / UNIT #:			_ CAPACITY:				_						ļ
ENGINE MAKE:			_ AXLE QUANTITY:_				_						ļ
MODEL:			single	tandem	tride	m							
TRUCK TYPE:	Straight		HUB REDUCTION (PLANETARY)		Yes								1
I	Semi				No								l
BODY TYPE: When Using FLR Kit	Steel		AXLE END STUD S				-						ا
Which osing	Aluminum		AXLE END STUD C				-						
SYSTEM VOLTAGE:	12 volt		TIRE SIZE:				_						
I	24 volt				single								
PICKER / SELF LOADER / CRANE					dual								
	No	_	SUSPENSION MAI	KE:			-						
OPEN OUTSIDE FRAME ROOM (18" / 40 cm min)	Yes		MODEL:										
	No		AIR RIDE:		Yes								
AIR COMPRESSOR MAKE:					No								
MODEL:						_							
CAPACITY:	_												
TO STATE OF STATE	L/min												
AIR DRYER(S) MAKE:													
MODEL:	_ single dual												
	Complete and return to M&M Service Inc. Fax (+1) 506-473-6472 or E-mail: luc@mmservice.ca												